




## PRODUCT DATA SHEET

NOVITANE® • SHEETING • CONVEYOR BELTING • CUSTOM PRODUCTS

# NOVITANE PLANER SLOW DOWN BELTS



NOVEX manufactures a *premium* line of **NOVITANE** thermoset polyurethane covered Planer Slow Down Belts for high production volume softwood lumber sawmills. Specially formulated 65 and 75 Durometer, Shore A Hardness *non-marking* belt cover surfaces are designed to provide the ultimate in slow down capability with their high coefficient of friction cover surfaces and will outwear pure gum covered belts by a factor of 3:1 providing exceptionally long service life. The polyurethane saturated solid woven polyester belt carcass enhances the belt's integrity, while providing a low coefficient of friction on its bottom surface making it ideal for slider bed service. The 150 PIW fabric is available in widths up to 96" and the 200 PIW fabric in widths up to 76" without a longitudinal splice.

# NOVITANE

## PLANER SLOW DOWN BELTS

**NOVITANE® • SHEETING • CONVEYOR BELTING • CUSTOM PRODUCTS**

### Features:

- Will out wear Pure Gum covered belts by a factor of 3:1
- Specially formulated wear resistant **non-marking** thermoset urethane belt covers in 2 different hardnesses with a high coefficient of friction
- **Seamless** vulcanized endless splices provide longer belt service life
- All PSD belts can be hot air welded endless on the conveyor system
- Accidental belt tears can be quickly repaired by utilizing a hot air gun and **NOVITANE** weld rod
- **NOVITANE** PSD belts will weigh approximately 33% less than Pure Gum covered belts making installation easier

### NOVITANE Planer Slow Down Belt Specification Data:

Specification	Tension Rating PIW	OAG	Max. Belt Width	Min. Pulley Diameter	Color
IG-150/65-COS(16)	150	1/4"	96"	6"	Clear
IG-150/75-COS(16)	150	1/4"	96"	6"	Black
IG-200/65-COS(24)	200	3/8"	76"	8"	Clear
IG-200/65-COS(28)	200	7/16"	76"	10"	Clear

